



**NOTES:**

1. DIG PLANTING HOLE TWICE THE DIAMETER OF THE ROOTBALL. IF IMPERVIOUS MATERIAL IS ENCOUNTERED , AUGER 12" DIAMETER DRAINAGE HOLE PER STANDARD SPECIFICATIONS.
2. PROVIDE 30"-36" DIAMETER CIRCULAR GRASS FREE AREA, CENTERED ON TREE.
3. PROVIDE 6" HIGH (MIN) TRUNK SHIELD.
4. SET TREE WITH TOP OF ROOTBALL APPROXIMATELY 1" ABOVE PLANTING GRADE. IF NECESSARY, ADJUST BOTTOM OF HOLE WITH BACKFILL MIX TO RAISE ROOTBALL. SCORE SIDES OF ROOTBALL APPROXIMATELY 1" DEEP TO PREVENT CIRCLING ROOTS.
5. FILL PLANTING HOLE TO PLANTING GRADE WITH BACKFILL MIX AS SPECIFIED, COMPACT LIGHTLY.
6. FOR DECIDUOUS TREES, DRIVE 2 TREE STAKES, 1 SOUTHWEST AND 1 NORTHEAST OF TREE. STAKES SHOULD BE 12" FROM TREE AND SET WITH TOP BELOW CROWN OF TREE. FOR CONIFERS, DRIVE STAKE NORTHWEST OF TREE.
7. SUPPORT TREE USING RUBBER TIE STRAPS NAILED TO TREE STAKES.



# CITY OF CLOVIS

## TREE PLANTING-TURF AREAS

DWG NO.  
**P-13**

REF:  
STD. SPECIFICATIONS  
SECTION 20  
LANDSCAPE PLANTING

APPROVED BY:		NO.	REVISED	BY	APPROVALS	SCALE: NTS
CITY ENGINEER			01-19-11	BGJ	CM DRU PUD	DRAWN BY: JA
DATE:	4/29/11				OTHER _____ OTHER _____ OTHER _____	SHEET 1 OF 1