



**NOTES:**

1. DIG PLANTING HOLE TWICE THE DIAMETER OF THE ROOTBALL. IF IMPERVIOUS MATERIAL IS ENCOUNTERED , AUGER 12" DIAMETER DRAINAGE HOLE PER STANDARD SPECIFICATIONS.
2. FORM A 3" DEEP CIRCULAR BASIN AROUND TREE.
3. INSTALL IRRIGATION FACILITIES AS SPECIFIED.
4. SET TREE WITH TOP OF ROOTBALL APPROXIMATELY 1" ABOVE PLANTING GRADE. IF NECESSARY, ADJUST BOTTOM OF HOLE WITH BACKFILL MIX TO RAISE ROOTBALL. SCORE SIDES OF ROOTBALL APPROXIMATELY 1" DEEP TO PREVENT CIRCLING ROOTS.
5. FILL PLANTING HOLE TO PLANTING GRADE WITH BACKFILL MIX AS SPECIFIED, COMPACTING LIGHTLY.
6. COVER WITH 2" OF MULCH WHEN SPECIFIED.
7. FOR DECIDUOUS TREES, DRIVE 2 TREE STAKES, 1 SOUTHWEST AND 1 NORTHEAST OF TREE. STAKES SHOULD BE 12" FROM TREE AND SET WITH TOP BELOW CROWN OF TREE. FOR CONIFERS, DRIVE 1 STAKE NORTHWEST OF TREE.
8. SUPPORT TREE USING RUBBER TIE STRAPS NAILED TO TREE STAKES.



# CITY OF CLOVIS

DWG NO.  
**P-14**

## TREE PLANTING - NON TURF AREAS WITH ROOT BARRIER

REF:  
STD. SPECIFICATIONS  
SECTION 20  
LANDSCAPE PLANTING

APPROVED BY:	NO.	REVISED	BY	APPROVALS	SCALE: NTS
CITY ENGINEER DATE: <i>4/29/11</i>		01-27-11	BGJ	CM	OTHER _____
		06-15-11	BGJ	DRU	OTHER _____
				PUD	OTHER _____
					DRAWN BY: JA
					SHEET 1 OF 1