



**NOTES:**

1. DIG PLANTING HOLE TWICE THE DIAMETER OF THE ROOTBALL TO DEPTH EQUAL TO PLANNED DEPTH OF ROOTBALL. IF IMPERVIOUS MATERIAL IS ENCOUNTERED, AUGER 12" DIAMETER DRAINAGE HOLE PER STANDARD SPECIFICATIONS.
2. SET SHRUB WITH TOP OF ROOTBALL APPROXIMATELY 1" ABOVE FINISH GRADE. IF NECESSARY, ADJUST BOTTOM OF HOLE WITH BACKFILL TO RAISE ROOTBALL. CUT SIDES ROOTBALL TO MIDDLE OF ROOTBALL AT 3 EQUIVALENT LOCATIONS TO PREVENT CIRCLING ROOTS.
3. BACKFILL HOLE TO FINISH GRADE WITH NATIVE SOIL REMOVED FROM PLANTING HOLE; REMOVE ROCKS, HARDPAN, DELETERIOUS MATERIAL. COMPACT LIGHTLY.
4. WHEN SPECIFIED, COVER WITH 1" THICK MULCH LAYER; KEEP CLEAR OF TRUNK BASE; FORM A BERMED 2" DEEP CIRCULAR BASIN AROUND SHRUB.



# CITY OF CLOVIS

DWG NO.  
**P-16**

## SHRUB PLANTING

REF. STANDARD SPEC  
SECTION 20  
LANDSCAPE PLANTING

APPROVED BY:	NO.	REVISED	BY	APPROVALS			SCALE: NTS
		01-19-11	BGJ	CM	OTHER	OTHER	DRAWN BY: JA
CITY ENGINEER				DRU	OTHER	OTHER	SHEET 1 OF 1
DATE:				PUD	OTHER	OTHER	