



NOTES:

1. MAINTAIN 12" SEPARATION BETWEEN BOXES, AND FROM CONCRETE IMPROVEMENTS. BOXES TO BE PARALLEL TO EACH OTHER AND PERPENDICULAR TO CONCRETE IMPROVEMENTS.
2. WHEREVER POSSIBLE, BOXES SHOULD BE LOCATED IN GROUND COVER OR SHRUB AREAS RATHER THAN TURF AREAS.
3. TOP OF BOXES TO BE SET 1" ABOVE GROUND IN GROUND COVER AND SHRUB AREAS, OR EVEN WITH GROUND LEVEL IN TURF AREAS.
4. VALVES, ETC. TO BE CENTERED INSIDE BOXES TO FACILITATE SERVICING.
5. AVOID HEAVILY COMPACTING SOIL AROUND BOXES TO PREVENT COLLAPSING OR DEFORMING SIDES OF THE BOXES.



CITY OF CLOVIS

DWG NO.
P-2

VALVE BOX LOCATION

REF: STD. SPECS
SECTION 21, LANDSCAPE
IRRIGATION SYSTEMS

APPROVED BY:	NO.	REVISED	BY	APPROVALS			SCALE: NTS
CITY ENGINEER		01-19-11	BGJ	CM	OTHER		DRAWN BY: JA
DATE: 7/19/11				DRU	OTHER		SHEET 1 OF 1
				PUD	OTHER		