


MEDIAN DETAIL

NOTES:

1. FORMED CURB SHALL BE CLASS 3 CONCRETE; EXTRUDED CURBS SHALL BE CLASS 2.
2. CURBS SHALL BE BROOM FINISH.
3. COMPACT MEDIAN FILL MATERIAL TO 90% UNDER SURFACES TO BE PAVED.
4. MEDIAN FILL MATERIAL MAY VARY DEPENDING ON LANDSCAPING REQUIREMENTS.
5. FILL INSIDE MEDIAN BEFORE PLACING AND/OR COMPACTING MATERIAL IN THE TRAVELED WAY.
6. ALL COLORED STAMPED CONCRETE SHALL BE SEALED WITH TWO COATS OF "CLEAR SEAL 100", OR APPROVED EQUAL.

| | | | | | |
|---|----------------------------|----------|-----|---|--------------|
|  | CITY OF CLOVIS | | | | DWG NO. |
| | MEDIAN ISLAND CURB DETAILS | | | | ST-25 |
| (NEW AC PAVEMENT) | | | | REF.: STD. SPECIFICATIONS | |
| APPROVED BY: | NO. | REVISED | BY | APPROVALS | SCALE: NTS |
| CITY ENGINEER <i>[Signature]</i> DATE: <i>6/29/17</i> | | 3-26-12 | PAA | CM <i>[Signature]</i> DRU <i>[Signature]</i> PUD <i>[Signature]</i> | DRAWN BY: JA |
| | | 05-29-12 | PAA | | SHEET 1 OF 1 |
| | | 09-28-12 | PAA | | |
| | | 06-12-17 | CGV | | |