



NOTES:

1. ITS COMMUNICATION HUB SHALL BE INSTALLED IN A LOCATION APPROVED BY CITY ENGINEER. COMMUNICATION HUB CABINET SHOULD BE AS NEAR TO N48T ITS VAULT AS POSSIBLE.
2. ITS INTERSECTION COMMUNICATIONS CABINET PER CURRENT CITY OF CLOVIS STANDARDS.
3. ITS CONDUITS TO BE INSTALLED PER PLANS AND AS DIRECTED BY THE ENGINEER.
4. TWO 4" DIAMETER TYPE 1 CONDUIT.
5. TWO 3" ITS HDPE CONDUITS INSTALLED PER STD. DWG. ITS-4, TYP.
6. INSTALL SERVICE PEDESTAL (TESCO 26-100 OR APPROVED EQUAL) AT LOCATIONS REQUIRING A HUB CABINET. SEE STD. DWG TS-5.
7. N48T ITS VAULT, SEE STD. DWG. ITS-4.
8. FOR TRAFFIC SIGNAL EQUIPMENT LAYOUT, SEE TRAFFIC SIGNAL (TS) STD. DRAWINGS.
9. CALTRANS #3 1/2E PULLBOX (OR AS SHOWN ON PLANS).



CITY OF CLOVIS

DWG NO.
ITS-2

TYPICAL ITS INTERSECTION LAYOUT WITH HUB

REF. STD. SPECIFICATIONS:
SECTION 82 & 86

APPROVED BY: CITY ENGINEER DATE: 1/16/2020	NO.	REVISED	BY	APPROVALS	SCALE: NTS
		08-04-11	BGJ	CM	OTHER _____
		09-22-11	BGJ	DRU	OTHER _____
	4	07-25-19	CGV	PUD	OTHER _____
					DRAWN BY: JA
					SHEET 1 OF 1