

ANCHOR TO BE INSTALLED NO MORE THAN 2½" ABOVE GRADE

TWO CORNER BOLTS SHALL BE USED TO SECURE POST TO SLEEVE

Ø7/16" HOLES (4 SIDES)

2-1/2" X 2-1/2" X 12 GA. @ 12" LONG SLEEVE

FILLET WELD ALL AROUND

FILLET WELD ALL AROUND

NOTE:

POST ANCHOR SHALL BE 30" ANCHOR-MATE W/12" SLEEVE, ULTIMATE HIGHWAY PRODUCTS, INC. OR APPROVED EQUAL.

2-1/4" X 2-1/4" X 12 GA. @ 30" LONG STEEL TUBE

EXPLODED VIEW

SIDE VIEW

NOTES:



1. ANY HOLES BELOW TOP TWO HOLES SHALL BE COVERED WITH DUCT TAPE.
2. SECURE POST TO ANCHOR USING CORNER BOLT, SAMPLE PICTURED TO LEFT.



CITY OF CLOVIS

DWG NO.
ST-15A

STREET SIGN POST ANCHOR

REF.:
STD. SPECIFICATIONS
SECTION 84

APPROVED BY:	NO.	REVISED	BY	APPROVALS	SCALE: NTS	
CITY ENGINEER <i>[Signature]</i>		05-20-09	BGJ	CM <i>[Signature]</i>	DRAWN BY: JA	
		01-14-11	BGJ	DRU <i>[Signature]</i>		
	DATE: 6/6/19		09-28-12	PAA	PUD <i>[Signature]</i>	SHEET 1 OF 1
			03-20-19	CGV		