



NOTES:

1. SIGN LOCATION TO BE DETERMINED BY THE CITY ENGINEER.
2. R1-1 STOP SIGN TO BE 0.08" THICK ALUMINUM; FACE SHALL HAVE 3M #4090 DG-3 REFLECTIVE SHEETING W/ AN APPLIED 3M #1160 OR EQUAL GRAFFITI FILM. SIGN SHALL CONFORM TO CURRENT CAL MUTCD SPECIFICATIONS.
3. SQUARE POST AND ANCHOR FOR ALL INSTALLATIONS.
4. SEE CITY STD. DRAWING ST-11 FOR SIGN PLACEMENT.
5. SECURE POST TO ANCHOR USING TWO CORNER BOLTS. SEE CITY STD. DRAWING ST-15A.
6. ALL STREET NAME SIGNS TO BE 10' FROM GRADE.



CITY OF CLOVIS

DWG NO.
ST-19

STREET NAME & STOP SIGN INSTALLATION

REF.:
STD. SPECIFICATIONS
SECTION 84

APPROVED BY: CITY ENGINEER <i>[Signature]</i> DATE: 15:32:00-08'00'	NO.	REVISED	BY	APPROVALS	SCALE: NTS
	2	05-21-09 03-20-19 06-05-20	BGJ PAA CGV	CM DRU PUD	DRAWN BY: JA SHEET 1 OF 1