



NOTES:

1. SIGN LOCATION TO BE DETERMINED BY THE CITY ENGINEER.
2. R1-1 STOP SIGN TO BE 0.08" THICK ALUMINUM; FACE SHALL HAVE 3M #4090 DG-3 REFLECTIVE SHEETING W/ AN APPLIED 3M #1160 OR EQUAL GRAFFITI FILM. SIGN SHALL CONFORM TO CURRENT CAL MUTCD SPECIFICATIONS.
3. SQUARE POST AND ANCHOR FOR ALL INSTALLATIONS.
4. SEE CITY STD. DRAWING ST-11 FOR SIGN PLACEMENT.
5. SECURE POST TO ANCHOR USING TWO CORNER BOLTS. SEE CITY STD. DRAWING ST-15A



CITY OF CLOVIS

DWG NO.

ST-19

STREET NAME & STOP SIGN INSTALLATION

REF.:
STD. SPECIFICATIONS
SECTION 84

APPROVED BY:

NO.

REVISED

BY

APPROVALS

SCALE: NTS

CITY ENGINEER

DATE: 6/6/19

05-21-09

01-14-11

09-28-12

03-20-19

BGJ

BGJ

PAA

CGV

CM

DRU

PUD

DRAWN BY: JA

SHEET 1 OF 1