



# NOTES:

1. FORMED CURB SHALL BE CLASS 3 CONCRETE; EXTRUDED CURBS SHALL BE CLASS 2.
2. CURBS SHALL BE BROOM FINISH.
3. COMPACT MEDIAN FILL MATERIAL TO 90% UNDER SURFACES TO BE PAVED.
4. MEDIAN FILL MATERIAL MAY VARY DEPENDING ON LANDSCAPING REQUIREMENTS.
5. FILL INSIDE MEDIAN BEFORE PLACING AND/OR COMPACTING MATERIAL IN THE TRAVELED WAY.
6. ALL COLORED STAMPED CONCRETE SHALL BE SEALED WITH TWO COATS OF "CLEAR SEAL 100", OR APPROVED EQUAL.



## CITY OF CLOVIS MEDIAN ISLAND CURB DETAILS (EXISTING AC PAVEMENT)

DWG NO.  
**ST-25A**

REF.:  
STD. SPECIFICATIONS

APPROVED BY:

NO.

REVISED

BY

APPROVALS

SCALE: NTS

CITY ENGINEER

DATE:

6/29/17

3-26-12

05-29-12

09-28-12

06-12-17

PAA

PAA

PAA

CGV

CM

DRU

PUD

DRAWN BY: JA

SHEET 1 OF 1