

TYPICAL CORNER CONNECTIONS

NOTES:

1. INSTALL SINGLE CONDUCTOR COLOR CODED #14 THWN COPPER WIRE BETWEEN TERMINAL STRIP AND EACH SIGNAL ASSEMBLY AND CONNECT.
2. THE CABLES THAT COMPRISE A SIGNAL PHASE SHALL HAVE AN IDENTIFICATION BAND PLACED NEAR THE END OF TERMINATION POINTS AND IN EVERY PULL BOX. THE IDENTIFICATION BAND SHALL BE A 3/8" PLASTIC STRIP AND INSTALLED WITH NON-FERROUS PERMANENT FASTENER. ALL CABLES SHALL BE LABELED PER PHASING SHOWN ON PLANS.
3. ALL CRIMP STYLE LUGS AND THE ENDS OF STRANDED CONDUCTORS SHALL BE SOLDERED.






# CITY OF CLOVIS

DWG NO.  
**TS-4**

## VEHICLE SIGNAL TERMINAL LOCATION

REF.:  
STANDARD SPEC.  
SECTION 86

APPROVED BY:  CITY ENGINEER	NO.	REVISED	BY	APPROVALS	SCALE: NTS
		04-15-09	BGJ	CM 	DRAWN BY: JA
DATE: 5/19/2020	2	01-18-11	BGJ	DRU 	SHEET 1 OF 1
		02-12-19	CGV	PUD 